

HORIZONTAL AUTOCLAVE AUT22-200



HORIZONTAL AUTOCLAVE AUT22-200

Laboratory horizontal autoclaves are useful in bulk sterilization applications of equipment and materials in various industries and research institutions. Also for disposing biological waste, reducing the risk of contamination and sterile the waste before discarding. We provide a variety of horizontal autoclave according to applications, features and customers requirements.

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

AUT22-200 HORIZONTAL AUTOCLAVE

High Quality Stainless steel chamber with drying function

Safety features for over temperature and pressure

Equipped with a built in printer

Automatic opening of safety valve if pressure exceeds 0.24MPa

Door remains locked if pressure exceeds 0.027MPa

Over temperature, over pressure, auto protection device

Automatic power cut off and water cut off in case of water shortage



SPECIFICATIONS

Model	AUT22-200
Capacity	200 L
Adjustment of Temperature	40°C-134°C
Sterilization Temperature	134°C
Sterilization Time	0-99 min
Heat Average	±2°C
Working Pressure	0.22 MPa
Time of Drying	0-99 min
Chamber Dimension	515×1000 mm
Overall Dimension (LxWxH)	1400x670x1650 mm
Packing Size	860 x 1650 x 1900 mm
Weight	290/380 kg
Power	9000 W
Power Supply	380 V, 50Hz



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com