

TABLETOP CENTRIFUGE CEN15-05C



TABLETOP CENTRIFUGE CEN15-05C

These centrifuges are widely used in the fields of biochemistry, pharmacy, clinical medicine and other research fields for variety of separation needs. The programmable microprocessor centrifuge allows modification of the parameter during operation. In addition, accommodates various type of tubes or plates and size of the sample.

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuge, Laboratory Floor Type Centrifuge, Benchtop Centrifuge, Non Refrigerated High Speed Centrifuge, Laboratory Tabletop Centrifuge.

CEN15-05C TABLETOP CENTRIFUGE

LCD display

Automatic Blood Collection Tube Decapping at the end of the process, prevent user from being infected by pathogenic bacteria.

Brushless DC motor

Inner chamber material: Stainless Steel

Electronic door interlock

Memory of 12 programs

19 levels of acceleration and 19 levels of deceleration



SPECIFICATIONS

Model	CEN15-05C
Maximum Capacity (No of tubes x Vol.)	4X250 ml
Maximum Speed RPM	5000
Speed Accuracy	± 10 rpm
Maximum RCF	5200xg
Timer Range	1~9999 min 59 s, Pulse, Continuous
Acceleration Rate	19
Deceleration Rate	19
Drive System	Direct, induction motor drive
Overall Dimension	450x550x365 mm
Program	12 user-defined
Noise Level	≤ 60 dB(A)
Weight (Net/Gross)	45 kg
Power	600 W
Power Supply	AC 200-240V, 50/60Hz or AC 100-130V, 50/60Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Description	Capacity	RPM	RCF _{xg}
LS52218	Swing-out Rotor	Blood collection tube	56x2-7ml	4000	3400xg
LS52569	Swing-out Rotor	Blood collection tube	80x2-7ml	4000	3400xg

LS52854	Swing-out Rotor	4x250 ml		5000	5200 Xg
LS54335	Swing-out Rotor	Blood collection tube	32x2-7ml	4000	3100xg



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA
Email: info@labtare.com | Website: labtare.com