

MICROCENTRIFUGE CEN42-072



MICROCENTRIFUGE CEN42-072

This compact, powerful micro centrifuge is useful to separate or sediment small volume samples at high speed. The short-spin key, soft brake, FastTemp features optimizes the overall function of the centrifuges. Faults are diagnosed automatically and displays fault code. These hybrid micro-centrifuge can run PCR tubes, Capillary tubes along with standard tubes.

Used in Molecular Biology Separations, Clinical, Labs, Biochemistry, Tissue Culture, Genomics, Drug discover.
Also known as Benchtop Centrifuge, Laboratory Centrifuge.

CEN42-072 MICROCENTRIFUGE

Low noise, <47dB

Rotors are easily interchangeable

The maximum RCF can be 3200xg

There are two ways to stop the machine, one is free stop which takes less than 15 seconds and other way is cover braking which takes 3 seconds.

Low wind resistance with slow temperature increase

Filtration and voltage regulation function

well designed shock absorber with very lower vibration



SPECIFICATIONS

Model	CEN42-072
Maximum Capacity (No of tubes x Vol.)	8x1.5 ml / 2.0 ml
Maximum Speed RPM	7200
Maximum RCF	810-3260xg
Speed Control	Automatic / Constant Speed
Brake System	Dynamic Braking
Drive System	Direct Drive / Vibration
Power Supply	AC85V-250V 1A 50 / 60 Hz



Labtare USA

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA

Email: info@labtare.com | Website: labtare.com