

# MICROCENTRIFUGE CEN44-148



# MICROCENTRIFUGE CEN44-148

This compact, powerful micro centrifuge is useful to separate or sediment small volume samples at high speed. The short-spin key, soft brake, FastTemp features optimizes the overall function of the centrifuges. Faults are diagnosed automatically and displays fault code. These hybrid micro-centrifuge can run PCR tubes, Capillary tubes along with standard tubes.

Used in Molecular Biology Separations, Clinical, Labs, Biochemistry, Tissue Culture, Genomics, Drug discover.  
Also known as Benchtop Centrifuge, Laboratory Centrifuge.

## CEN44-148 MICROCENTRIFUGE

- The maximum RCF can be 1700xg
- Acceleration/Deceleration: <18 seconds
- LCD display
- Rotors are in autoclavable aluminium material
- Short-spin key for quick centrifugation
- Brushless DC motor
- Low noise
- Electronic lock



## SPECIFICATIONS

Model	CEN44-148
Maximum Capacity (No of tubes x Vol.)	24x1.5/2ml
Maximum Speed RPM	14800
Maximum RCF	17100xg
Timer Range	15 S~99 min
Acceleration/ Deceleration	18s↑18s↓
Overall Dimension	230x210x150 mm
Weight (Net/Gross)	8 kg
Power	200 W
Power Supply	110V-240V 50-60 Hz

## ACCESSORIES

Accessory Code	Name	Description
LS55202	Rotor	24x1.5/2.0 ml





**Labtare USA**

82 Wendell Avenue, STE 100, Pittsfield, MA, 01201, USA  
Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)