

# MOISTURE ANALYZER LTANA12-11



# MOISTURE ANALYZER LTANA12-11

Also known as Laboratory Moisture Analyzer, Moisture Balance, Moisture Meter, Halogen Moisture analyzer, Laboratory Moisture Balance, Laboratory Halogen Moisture analyzer.

## LTANA12-11 MOISTURE ANALYZER

- Halogen Heating
- Pan size:  $\varphi$  100mm
- 3.7 inch touch screen
- Long distance operated
- Stainless steel chamber
- Easy cleaning after testing
- Temperature and time can be set
- The percentage of moisture content
- Max 230 degree heating temperature
- Automatic opens the heating chamber



## SPECIFICATIONS

Model	LTANA12-11
Weighing Range	210 g
Temperature	40°C-230°C
Operating Temperature Range	5°C-35°C
Temperature Set	1°C
Temperature Setting	40°C-230°C By 1°C Step
Moisture Range	0.00%-100.0%
Moisture Readability	0.0001
Dry Range	100.00%-0.00%
Dry Residual Readability	0.0001
Pan Size	$\Phi$ 100 mm
Readability	0.001 g
Interface	Cable, RS232/RJ45/USB
Heat Source	HALOGEN LAMP
Calibration	External Calibration
Rechargeable Battery	No
Temperature Sensor	PT-100
Display	7 inch touch panel
Operation Height	275 mm
The Chamber Height	35 mm
Dimension	215x195x415 mm
Indicator Dimension	200x75x135 mm
Number of History	20
Number of Storage	20
Power	400 W
Balance	Output: 9 V

Machine	Output: 24 V (Dual-drive)
Power Supply	220 V±15%, 110 V±15% / 50 Hz, 60 Hz



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)