



FLOOR STANDING HORIZONTAL AUTOCLAVE LTAUT15-2

Used in Bulk sterilization, Microbiology Lab, Research Institutions, Laboratory, Pharmaceutical, Food industry, Chemical industry.

Also known as Laboratory Sterilizer, Horizontal Pressure Sterilizer, Laboratory Horizontal Autoclave,.

LTAUT15-2 FLOOR STANDING HORIZONTAL AUTOCLAVE

High Quality Stainless steel chamber with drying function
Safety features for over temperature and pressure
Equipped with a built in printer
Automatic opening of safety valve if pressure exceeds 0.24MPa
Door remains locked if pressure exceeds 0.027MPa
Over temperature, over pressure, auto protection device
Automatic power cut off and water cut off in case of water shortage



SPECIFICATIONS

Model	LTAUT15-2
Capacity	200 L
Adjustment of Temperature	40°C-134°C
Sterilization Temperature	134°C
Sterilization Time	0-99 min
Heat Average	≤±2°C
Working Pressure	0.22 MPa
Time of Drying	0-99 min
Chamber Dimension	515x1000 mm
Overall Dimension (LxWxH)	1400x670x1650 mm
Packing Size	860 x 1650 x 1900 mm
Weight	290/380 kg
Power	9000 W
Power Supply	380 V, 50Hz



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com