

# FLOOR STANDING VERTICAL AUTOCLAVE LTAUT36-4



# FLOOR STANDING VERTICAL AUTOCLAVE

## LTAUT36-4

### LTAUT36-4 FLOOR STANDING VERTICAL AUTOCLAVE

- Three times pre-vacuum
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- LED touch screen display
- Standard test interface
- Self-expanding seal
- With drying function
- With stainless steel bucket or basket
- With automatic protection function: over temperature protection; over pressure self discharge protection ; low water level protection; anti dry burning.
- Automatic water
- External steam Generator
- Buzzer reminder after sterilization, automatic stop.
- Automatic discharge of cold air, automatic steam exhaust after sterilization
- Internal printer



### SPECIFICATIONS

Model	LTAUT36-4
Capacity	100 L
Power	4.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 450x650
Bucket dimension	Ø 420x540
Basket dimension	Ø 410x300x2
Outer dimension	760x560x1260
Packing size	870x650x1380
Net weight	132 Kg
Gross Weight	159 Kg



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)