

# FLOOR STANDING VERTICAL AUTOCLAVE LTAUT37-3



# FLOOR STANDING VERTICAL AUTOCLAVE

## LTAUT37-3

### LTAUT37-3 FLOOR STANDING VERTICAL AUTOCLAVE

- Hand wheel translation and quick opening structure
- High quality stainless steel material
- With drying function
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Safety interlocking device
- Digital display and Touch buttons
- Standard test interface
- Self-expanding seal
- With automatic protection function over temperature protection; over pressure self discharge protection ; low water level protection; anti dry burning
- With stainless steel bucket or basket
- Buzzer reminder after sterilization, automatic stop
- Automatic discharge of cold air, automatic steam exhaust after sterilization, Internal steam cycle



### SPECIFICATIONS

Model	LTAUT37-3
Capacity	75 L
Power	4.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 400x625
Bucket dimension	Ø 380x560
Basket dimension	Ø 360x280x2
Outer dimension	725x525x1170
Packing size	840x610x1310
Net weight	114 Kg
Gross Weight	145 Kg



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)