

FLOOR STANDING VERTICAL AUTOCLAVE LTAUT38-1



FLOOR STANDING VERTICAL AUTOCLAVE

LTAUT38-1

LTAUT38-1 FLOOR STANDING VERTICAL AUTOCLAVE

- Hand wheel translation and quick opening structure
- High quality stainless steel material
- Microcomputer automatic control, arbitrary setting sterilization parameters
- Yr Safety interlocking device
- Digital display and Touch buttons
- Standard test interface
- Self-expanding seal
- With drying function
- With automatic protection function:over temperature protection; over pressure protection; low water level protection; anti dry burning
- With stainless steel bucket or basket Buzzer reminder after sterilization, automatic stop
- Automatic discharge of cold air,automatic steam exhaust after sterilization



SPECIFICATIONS

Model	LTAUT38-1
Capacity	35 L
Power	3.5 kW
Voltage	AC 220V. 50HZ
Design pressure	0.25 Mpa
Design temperature	139°C
Rated working pressure	0.22 Mpa
Rated working temperature	134°C
Sterilization temperature setting range	116°C-134°C
Sterilization time setting range	4 ~ 120 min
Drying time setting range	0 ~ 240 min
Chamber volume	Ø 350x400
Bucket dimension	Ø 330x320
Basket dimension	Ø 320x350
Outer dimension	480x480x1000
Packing size	580x630x1130
Net weight	58 Kg
Gross Weight	79 Kg



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com