

DRY BATH INCUBATOR LTBAT21-11



DRY BATH INCUBATOR LTBAT21-11

Used in Pharmaceutical, Chemical, Food Safety, Environment, Quality inspection, Laboratory.
Also known as Laboratory Dual Temperature Dry Bath Incubators.

LTBAT21-11 DRY BATH INCUBATOR

Unique dual temperature control slot can individually control temperature to make sure noninterference. One equipment to meet the demand for more experiments.

OLED display, simple interface, double time and temperature setting, means simultaneous temperature and diminishing time display.

Fast heating speed, uniform heating, accurate temperature control, high stability, low energy consumption and no noise.

Built in temperature calibration function, automatic fault detection and buzzer alarm function.

Built in over-temperature protection device, safe and reliable, enhance the service life of the machine.

Product designed compact and tight, occupied little space. Using freer and easier.

Various blocks for convenient replacement, easy for cleaning and disinfection.

Perfect high module sealing cartridge with cover can make 15/50ml high module totally enclosed with dry bath.

Heated model can option external sensors to control temperature more accurately and directly.



SPECIFICATIONS

Model	LTBAT21-11
Capacity	22.5 L
Function	Power adjustable
Temperature Range	-5 °C~105 °C (If Ambient Temperature≤20 °C) 0°C~105°C (If Ambient Temperature≤25 °C) 4°C~105 °C (If Ambient Temperature≤30 °C)
Temperature Accuracy for blocks	±0.5°C
Temperature Uniformity	±0.5°C(within the blocks)
Display Accuracy	0.1°C
Cleaning Tank (LxWxH)	500x300x150 mm
Outer Dimension (WxDxH)	640x340x370 mm
Weight	3.0 kg
Lid's Temperature range	RT+5-110°C
Maximum Input Power	750
Maximum Output Power	720
Heating Power	NO
Power Adjustable (%)	30-100
Drain	YES
Level Control System	YES



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com