

DRY BATH INCUBATOR LTBAT21-7



DRY BATH INCUBATOR LTBAT21-7

Used in Pharmaceutical, Chemical, Food Safety, Environment, Quality inspection, Laboratory.

Also known as Laboratory Dual Temperature Dry Bath Incubators.

LTBAT21-7 DRY BATH INCUBATOR

Microprocessor controlled incubation temperature and time

Compact design with stable operation

Rapid heat up, uniform heating, high stability, low energy consumption and noise

Simultaneous display of set temperature and time

Built in temperature calibration function

Aluminium blocks ensures even heat distribution, eliminating the possibility of heater burnout

Custom blocks available to meet experimental requirements

Easy cleaning, replacement and disinfection of metal blocks

Automatic fault detection and buzzer alarm function

Audio alarm indicates program completion

Over temperature protection device



SPECIFICATIONS

| | |
|------------------------|---|
| Model | LTBAT21-7 |
| Temperature Range | -10-100 °C |
| Temp. Max. Decrease | R.T. decreases 30°C@R.T. 26°C |
| Temp. Setting Range | -10 °C ~100 °C |
| Temp. Stability@100°C | ±0.5 °C |
| Temp. Stability@40°C | ±0.3 °C |
| Block Temp. Uniformity | ±0.3°C |
| Temp. Display Accuracy | 0.1°C |
| Heating Speed | ≤15min (20°C to 100°C) |
| Cooling Speed | ≤30min (R.T. decreases 30°C) @R.T. 26°C |
| Time Range | 1 min ~ 99 h 59 min or continuous |
| Voltage | AC90~230 V, 50/60 Hz |
| Power | 150 W |
| Fuse | 250 V, 3A, φ5x20 |
| Dimension | W.196 x D.270 x H.170mm |
| Net Weight | 3.5 kgs |



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com