

DRY BATH INCUBATOR LTBAT23-22



DRY BATH INCUBATOR LTBAT23-22

Used in Clinical, General Chemistry, Preservation, Reactions of sample, DNA amplification, Initial Denaturation of electrophoresis, Laboratory.

Also known as Digital Heating Blocks, Laboratory Mini Dry Bath Incubators.

LTBAT23-22 DRY BATH INCUBATOR

Novel and unique appearance, simple interface operation, small size. Temp. Max. Decrease of 25°C @ R.T. 26°C.

Using 5-inch TFT high-definition full-touch color screen, can quickly edit the required documents, temperature curve visual display, the setting is convenient and fast, real-time accurate display temperature curve and instrument operation process status.

Refrigeration type is based on semiconductor heating and cooling technology, and PID temperature control technology design, the rate of heating and cooling is excellent.



SPECIFICATIONS

Model	LTBAT23-22
Block temp. setting range	- 10 °C ~ 100 °C
Block temp. control range	(R.T.- 25°C)~100 °C
Temp. Max. Decrease	R.T. decreases 25°C@R.T. 26°C
Hot lid temp. setting range(≤105°C)	0~105 °C / Block+(0~105 °C)
Hot lid temp. control range	R.T.+5 °C~105 °C
Time range	1s ~99m59S / 0 is ∞
Max. number of steps	10
Max. number of cycles	99
Block temp. control accuracy	±0.5 °C
Hot lid temp. accuracy	±1.0 °C
Block temp. uniformity	±0.5 °C
Display accuracy	0.1 °C
Heating time (R.T.25 °C)	Heating rate(37°C-100°C)≥7°C/min
Cooling time	Cooling rate(100°C-37°C)≥8°C/min
Dimension	W.185xD.280xH.160 mm
Net weight	3.2 Kgs

LABTARE

Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com