

# MINI DRY BATH LTBAT25-14



# MINI DRY BATH LTBAT25-14

Used in Immunoassays, Melting points, Enzyme reactions, Boiling points, Incubation, Activation of cultures, Laboratory procedures..

Also known as Digital Dry Bath Incubators, Heating blocks, Laboratory Dry Bath Incubators.

## LTBAT25-14 MINI DRY BATH

Microprocessor controlled incubation temperature and time

Compact design with stable operation

Rapid heat up, uniform heating, high stability, low energy consumption and noise

Simultaneous display of set temperature and time

Built in temperature calibration function

Aluminium blocks ensures even heat distribution, eliminating the possibility of heater burnout

Custom blocks available to meet experimental requirements

Easy cleaning, replacement and disinfection of metal blocks

Automatic fault detection and buzzer alarm function

Audio alarm indicates program completion

Over temperature protection device



## SPECIFICATIONS

Model	LTBAT25-14
Temperature Range	RT+5 °C-100 °C
Temp. Setting Range	0 °C~100 °C
Temp. Stability@100°C	±0.5 °C
Temp. Stability@40°C	±0.3 °C
Block Temp. Uniformity	±0.3 °C
Temp. Display Accuracy	0.1 °C
Heating Speed	≤15 min ( 20 °C to 100 °C)
Cooling Speed	fan cooling
Heating Cover	No
Time Range	1 sec~999 sec or 1 min~999 min
Voltage	DC24V adapter
Power	60 W
Dimension	W.110 x D.156 x H.103mm
Net Weight	1 kgs



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)