

# LOW TEMPERATURE CIRCULATOR LTBAT29-1



# LOW TEMPERATURE CIRCULATOR LTBAT29-1

## LTBAT29-1 LOW TEMPERATURE CIRCULATOR

P.I.D temperature controller provides accurate and reliable temperature control

Large LCD display screen and interface provides for user-friendly operation

Preset On/Off function

Independent circulating pump switch for easy starting/stopping the cycle

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean. Uniquely designed heating method can up to 80 °C

Programming setting function with 7 periods and 9 steps for each period, which means. There are 63 programmable steps in total



## SPECIFICATIONS

Model	LTBAT29-1
Capacity	5 L
Temperature range	-20 - 80°C
Temperature accuracy	±0.5°C
Cooling capacity at 10°C	530 W
Refrigerant	R404A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	1100 W
Power requirements	AC 220 V / 50 HZ
Pump power	30
Pump flow max.	6 L / min
Maximum head	9 m
Inlet/Outlet pipe diameter	Φ10 mm
Weight	32
Liquid storage	3.5
Noise level	≤45
Dimension	210Wx410Dx511H mm



**Labtare Analytical Instruments**

Email: [info@lbtare.com](mailto:info@lbtare.com) | Website: [lbtare.com](http://lbtare.com)