

CLASS II BIOLOGICAL SAFETY CABINET LTCBS10-1



CLASS II BIOLOGICAL SAFETY CABINET

LTCBS10-1

Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory.
Also known as Class II BSC, Biosafety Cabinet.

LTCBS10-1 CLASS II BIOLOGICAL SAFETY CABINET

Stainless Steel 304 table for operation

Digital LCD display for easy monitoring of all parameters

Emission of 253.7 nm for highly efficient decontamination

Motored front window with timer function

Two-layered marinated toughened glass ($\geq 5\text{mm}$) motorized front window

Negative air pressure provides personnel protection by constant movement of air in working area

Remote control operation including front sash movement and fan speed control

Foot switch to adjust the height of the front window

Centrifugal fan speed adjustable: H14 HEPA filter

Intrinsic sterilization is achieved after activating cabinet for 30 min via UV timing

Filter Life Indicator: Pressure value displayed to show life utility of main filter

Low noise and high energy efficiency for operational cost savings

Audio and visual alarm for filter replacement, front window over height and abnormal airflow



SPECIFICATIONS

Model	LTCBS10-1
Type	Class II, Type A2
Filter	HEPA Filter - Two, 99.995% efficiency at 0.3 μm . Filter life indicator
Inflow Velocity	0.53 \pm 0.025m/s
Down Flow Velocity	0.33 \pm 0.025m/s
Max Opening	370mm(15")
Tested Opening	Safety height 200mm(8")
Front Window	Motorized. Single Layer toughened glass 5mm. Anti UV.
Airflow System	70% air recirculation, 30% air exhaust
Main Body Material	Cold-rolled steel with anti-bacteria powder coating
Work Zone Material	304 stainless steel
Work Surface Height	750mm with optional base stand
UV Lamp	15W x1 UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination
LED Lamp	8W x2
Illumination	$\geq 1000\text{Lux}$
Display	LCD display
Control System	Microprocessor
Visual and Audio Alarm	Filter replacement, window over height, abnormal air flow velocity;High filter pressure alarm.
Standard Accessory	LED lamp x2, UV lamp x1, Remote control, Waterproof sockets x2
Optional Accessory	SS Water tap x1, SS Gas tap x1,Base stand

Waterproof Socket	Two, total load of two sockets: 500W
Noise	≤67dB
Internal Size (WxDxH)	600x500x540mm
External Size (WxDxH)	700x650x1230mm (without base stand)
Package Size (WxDxH)	Carton: 850x787x450mm Wood: 860x970x1420mm (with base stand) Carton: 730x787x1450mm Wood: 860x780x1420mm (without base stand)
Gross Weight	Carton: 140kg Wood: 160kg (with base stand) Carton: 120kg Wood:140kg (without base stand)
Power Supply	AC220V±10%, 50/60HZ;110V±10%, 60Hz

ACCESSORIES

Accessory Code	Name
6200808015	UV Lampx2

OPTIONAL ACCESSORIES

Accessory Code	Name	External Dimension	Package Size (mm)
2400808008	Infrared Sterilizer	150x95x210 mm	
2400808009	Airflow Tester		
2400808010	Formalin Fumigation Sterilizer		300x200x160 mm
2400808011	Ammonium Hydrogen Carbonate Neutralizer		300x200x160 mm
2400808012	Armrest		
2400808013	Laboratory Chair		
2400808014	Dust Particle Counter		
2400808015	Digital Sound Level Meter		
2400808016	Illumination Meter		
2400808017	Air Flow Anemometer		
2400808018	Protective Garment		
2400808019	Protective Gloves		



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com