

CLASS II BIOLOGICAL SAFETY CABINET LTCBS10-4



CLASS II BIOLOGICAL SAFETY CABINET

LTCBS10-4

Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory.
Also known as Class II BSC, Biosafety Cabinet.

LTCBS10-4 CLASS II BIOLOGICAL SAFETY CABINET



SPECIFICATIONS

Model	LTCBS10-4
Filter	HEPA Filter - Two, 99.995% efficiency at 0.3 μm , filter life Indicator
Air Flow Volume	462m/h (272cfm)
Inflow Downflow Exhaust	65%: 863m/h (507cfm) 35%: 462m/h (272cfm)
Max Opening	550 mm (22")
Work Surface Height	750 mm
Tested Opening	Safety height 200mm (8")
Front Window	Manual laminated toughened glass , Anti UV
Filter Guard Type	Aluminum alloy frame
UV Lamp	30W Germicidal UV lamp, Emission of 253.7nanometers for most efficient decontamination, UV timer, UV life indicator
LED Lamp	18Wx2
Illumination	≥ 1000 lux
Display	LCD Display
Noise	EN 12469 <65dB
Waterproof Socket	Two, total Consumption <500W
Ground Resistant	<0.10 Ω
Material	Working area: 304 Stainless steel Frame and decorative plate Cold roller steel with anti bacteria powder coating
Alarm	Abnormal airflow velocity, Filter replacement, Front window at unsafe height, High filter pressure alarm
AC Motor	One ECM motor, 230V acceptable, Speed adjustable, high efficiency and low power consumption
Standard Accessory	LED lamp*2, UV lamp*1, Base stand, SS water tap*1, SS gas tap*1, Drain valve, Waterproof sockets*2, Stainless steel J.V. bar with 10 hooks
Optional Accessory	Armrest, Airflow tester, Formalin fumigation sterilizer, Infrared sterilizer, Remote control, Electric height adjustable base stand, Motorized front windows

Internal Size (WxDxH)	1210x660x660 mm
External Size (WxDxH)	1383x775x2295 mm
Package Size (WxDxH)	1540x1080x1900 mm
Gross Weight	340 kg
Consumption	<650W
Power Supply	AC230 V, 50 Hz



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com