

CLASS II BIOLOGICAL SAFETY CABINET LTCBS9-1



CLASS II BIOLOGICAL SAFETY CABINET LTCBS9-1

Used in Cell culturing, Genetics, Microbiological, Research, Cell Biology, Molecular Biology, Plant, Laboratory.
Also known as Class II BSC, Biosafety Cabinet.

LTCBS9-1 CLASS II BIOLOGICAL SAFETY CABINET

Time reserve function

Stainless Steel 304 table for operation

Emission of 253.7 nm for highly efficient decontamination

Remote control operation including front sash movement and fan speed control

Motored front window with timer function

Two-layered marinated toughened glass ($\geq 5\text{mm}$) motorized front window

Negative air pressure provides personnel protection by constant movement of air in working area

Foot switch to adjust the height of the front window

2 waterproof sockets located inside panel

Automatic air speed adjustable with filter block

Filter Life Indicator: Pressure value displayed to show life utility of main filter

Interlock function: Fluorescent lamp, UV lamp and front window, Blower and front window, UV lamp and blower

Low noise and high energy efficiency for operational cost savings

Audio and visual alarm for filter replacement, front window over height and abnormal airflow velocity

LCD display: filter and UV lamp working time, Filter life, Exhaust filter and downflow filter pressure, Humidity and temperature, System working time, Inflow and downflow velocity etc.



SPECIFICATIONS

Model	LTCBS9-1
Type	Class II, Type A2
Filter	ULPA Filter - Two, 99.9995% efficiency at 0.12 μm , filter life indicator
Inflow Velocity	0.53 \pm 0.025 m/s
Down Flow Velocity	0.33 \pm 0.025 m/s
UV Lamp	30Wx1 UV timer, UV life indicator, emission of 235.7 nanometers for most efficient decontamination
LED Lamp	12Wx2
Illumination	≥ 1000 lux
Waterproof Socket	Two, total load of sockets: 500W
Work Surface Height	750 mm (Size can be customized according to requirements)
Tested Opening	Safety height 200 mm (8")
Max Opening	440 mm
Front Window	Motorized, two layer laminated toughened glass ≥ 6 mm, Anti UV
Airflow System	70% air recirculation, 30% air exhaust
Control System	Microprocessor
Caster	Footmaster Caster
Display	LCD Display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature, system working time etc.

Work Zone Material	304 Stainless steel
Main Body Material	Cold roller steel with anti bacteria powder coating
Visual and Audio Alarm	Abnormal airflow velocity, filter replacement, front window at unsafe height, high filter pressure alarm, abnormal power failure
Standard Accessory	LED lamp 2pcs, UV lamp 1 pc, Base stand Remote control, Foot switch, Drain valve, Waterproof Socket 2 pcs
Optional Accessory	Water and Gas tap, Electric Height adjustable base stand, Armrest
Noise	≤65dB
Internal Size (WxDxH)	940x600x660 mm
External Size (WxDxH)	1100x755x2200 mm
Package Size (WxDxH)	1230x1060x1840 mm
Gross Weight	220 kg
Consumption	600W
Power Supply	AC220V 50/60Hz ; 110 60Hz

ACCESSORIES

Accessory Code	Name
6200808015	UV Lampx2

OPTIONAL ACCESSORIES

Accessory Code	Name	External Dimension	Package Size (mm)
2400808008	Infrared Sterilizer	150x95x210 mm	
2400808009	Airflow Tester		
2400808010	Formalin Fumigation Sterilizer		300x200x160 mm
2400808011	Ammonium Hydrogen Carbonate Neutralizer		300x200x160 mm
2400808012	Armrest		
2400808013	Laboratory Chair		
2400808014	Dust Particle Counter		
2400808015	Digital Sound Level Meter		
2400808016	Illumination Meter		
2400808017	Air Flow Anemometer		
2400808018	Protective Garment		
2400808019	Protective Gloves		



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com