

BLOOD TYPING CENTRIFUGE LTCEN16-6



BLOOD TYPING CENTRIFUGE LTCEN16-6

Used in Cell Separation, Precipitation, Sample Processing, Clinical, Cell Culture, Microplate Processing, Biochemistry, medical diagnosis.

Also known as Floor Standing Centrifuges, Laboratory Floor Type Centrifuges, Benchtop Centrifuges, Non Refrigerated High Speed Centrifuges, Laboratory Tabletop Centrifuges.

LTCEN16-6 BLOOD TYPING CENTRIFUGE

Brushless DC motor

LED display

Microprocessor controller

The inner chamber is made up of stainless steel

Electronic door interlock

Faults are diagnosed automatically

Operating parameters can be modified during the operation

Stable operation



SPECIFICATIONS

Model	LTCEN16-6
Maximum Capacity (No of tubes x Vol.)	24 gel card
Maximum Speed	3840 rpm
Maximum RCF	1790xg
Drive System	Direct, induction motor drive
Overall Dimension	14.8x14.2x11.8 in / 37.5x36x30 mm
Noise Level	≤ 60 dB(A)
Weight (Net/Gross)	21 kg
Max. Power Consumption	100 W
Power Supply	AC 200-240 V, 50/60 Hz or AC 100-127 V, 50/60 Hz

OPTIONAL ACCESSORIES

Accessory Code	Name	Rotor Capacity
2501613008	No. 1 Swing-out Rotor	12 gel cards
2501613009	No. 2 Swing-out Rotor	24 gel cards



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com