# REFRIGERATED MICROCENTRIFUGE LTCEN24-3

<u>aa</u>aa

labtare.com

## REFRIGERATED MICROCENTRIFUGE LTCEN24-3

Used in Molecular Biology Separations, Clinical, Labs, Biochemistry, Tissue Culture, Genomics, Drug discover. Also known as Microfuges, Refrigerated Microcentrifuges, Laboratory Microcentrifuges.

### LTCEN24-3 REFRIGERATED MICROCENTRIFUGE

Microprocessor controller LCD display RCF can be set up directly, without RPM to RCF translation Memory of 9 programs 9 levels of acceleration and 9 levels of deceleration Servomotor was adopt for lid open & lid lock, emergency lid release. Aerosol-tight quick lock rotors for safe centrifugation of hazardous samples Inner chamber material: Stainless Steel Rotors are in aeronautical aluminum material Electronic door interlock and Automatic rotor identification and Imbalance protection Faults are diagnosed automatically, display fault code. Ergonomic operating and information panel. CFC-free refrigerants system (TECUMSEH EUROPE COMPRESSOR), with both precooling and standstill cooling function.



#### SPECIFICATIONS

Model	LTCEN24-3		
Maximum Capacity (No of tubes x Vol.)	12x5 ml		
Temperature Range	-10°C to 35°C		
Temperature Accuracy	± 1°C		
Maximum Speed	15000 rpm		
Speed Accuracy	± 10 rpm		
Maximum RCF	21630xg with 24x1.5/2.0 ml rotor / 4 x PCR-strips rotor		
Time Range	Count up or down		
Acceleration Rate	10		
Deceleration Rate	10		
Refrigeration System	CFC-Free		
Control System	Microprocessor		
Display	Full color touchscreen interface		
Programmability	via easy access touchscreen menu		
Drive System	Direct, induction motor drive		
Rotor Identification	Auto-ID Instant, immediately upon rotor insertion		
Program	16 user-defined		
Overall Dimension	11.2x15.7x11.2 in / 28.5x40x28.5 mm		
Noise Level	≤ 58 dB(A)		
Weight (Net/Gross)	21 kg		
Max. Power Consumption	800 W		
Power Supply	AC 200-240V, 50/60Hz or AC 100-127V, 50/60Hz		

#### **OPTIONAL ACCESSORIES**

Accessory Code	Name	Rotor Capacity	Max Speed (rpm)	Max RCF(g)
2502410008	No. 1 Fixed-Angle Rotor	24x1.5/2.0 ml(with adapters for 0.2/0.5ml tube)	15000 rpm	21630Xg
2502410009	No. 2 Fixed-Angle Rotor	4xPCR-Strips	15000 rpm	21630Xg
2502410010	No. 3 Fixed-Angle Rotor	12x5 ml	15000 rpm	18270Xg



#### Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com