

RECIRCULATING CHILLER WATER COOLED LTCHI10-4



RECIRCULATING CHILLER WATER COOLED LTCHI10-4

LTCHI10-4 RECIRCULATING CHILLER WATER COOLED

P.I.D temperature controller provides accurate and reliable temperature control

Large LCD display screen and interface provides for user-friendly operation

Preset On/Off function

Independent circulating pump switch for easy starting/stopping the cycle

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean



SPECIFICATIONS

| | |
|-------------------------------|--|
| Model | LTCHI10-4 |
| Storage tank maximum capacity | 5 L |
| Temperature range | -20-20°C |
| Ambient temperature range | +5-30°C |
| Temperature accuracy | ±0.5°C |
| Cooling capacity at 20°C | 1.95 Kw |
| Cooling capacity at 0°C | 1.2 Kw |
| Cooling capacity at -20°C | 0.65 Kw |
| Refrigerant | R404A |
| Security features | Delay, leakage, overcurrent, overvoltage |
| Total power | 1350 W |
| Power requirements | AC220 V ± 10% / 50 HZ |
| Pump flow max. | 8 L/min |
| Maximum head | 1.5 m |
| Inlet/Outlet pipe diameter | Φ16 |
| Noise level | ≤45 |
| Liquid tank opening / depth | Φ220x180 mm |
| Dimensions | 315Wx540Dx625H mm |

LABTARE

Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com