

RECIRCULATING CHILLER WATER COOLED LTCHI11-1



RECIRCULATING CHILLER WATER COOLED

LTCHI11-1

LTCHI11-1 RECIRCULATING CHILLER WATER COOLED

P.I.D temperature controller provides accurate and reliable temperature control

Large LCD display screen and interface provides for user-friendly operation

Preset On/Off function

Independent circulating pump switch for easy starting/stopping the cycle

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean

Uniquely designed heating method can up to 80 °C



SPECIFICATIONS

Model	LTCHI11-1
Storage tank maximum capacity	3 L
Temperature range	-20-40°C
Ambient temperature range	+5-30°C
Temperature accuracy	±3°C
Cooling capacity at 20°C	1.5 Kw
Cooling capacity at 0°C	1.05 Kw
Cooling capacity at -20°C	0.45 Kw
Refrigerant	R404A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	1500 W
Heating power	550 W
Power requirements	AC 220 V ± 10% /50 HZ
Pump flow max.	8 L/min
Maximum head	1.5 m
Inlet/Outlet pipe diameter	Φ16
Noise level	≤45
Liquid tank opening / depth	Φ180x120 mm
Dimensions	250Wx480Dx585H mm



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com