

# RECIRCULATING CHILLER WATER COOLED LTCHI11-11



# RECIRCULATING CHILLER WATER COOLED

## LTCHI11-11

### LTCHI11-11 RECIRCULATING CHILLER WATER COOLED

P.I.D temperature controller provides accurate and reliable temperature control

Large LCD display screen and interface provides for user-friendly operation

Preset On/Off function

Independent circulating pump switch for easy starting/stopping the cycle

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean

Uniquely designed heating method can up to 80 °C



### SPECIFICATIONS

Model	LTCHI11-11
Storage tank maximum capacity	20 L
Temperature range	-30-40°C
Ambient temperature range	+5-30°C
Temperature accuracy	±3°C
Cooling capacity at 20°C	3.52 Kw
Cooling capacity at 0°C	2.96 Kw
Cooling capacity at -20°C	1.3 Kw
Refrigerant	R404A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	3800 W
Heating power	2000 W
Power requirements	AC 220 V ± 10% /50 HZ
Pump flow max.	17 L/min
Maximum head	2.5 m
Inlet/Outlet pipe diameter	Φ20
Noise level	≤55
Liquid tank opening / depth	Φ300x300 mm
Dimensions	430Wx600Dx840H mm



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)