

# RECIRCULATING CHILLER WATER COOLED LTCHI11-6



# RECIRCULATING CHILLER WATER COOLED

## LTCHI11-6

### LTCHI11-6 RECIRCULATING CHILLER WATER COOLED

P.I.D temperature controller provides accurate and reliable temperature control

Large LCD display screen and interface provides for user-friendly operation

Preset On/Off function

Independent circulating pump switch for easy starting/stopping the cycle

Easy to set Adjustable Timer. (1 minute to 5,999 minutes)

Maintenance-free operation with easy to clean surface

Both heater and bath chamber are made of corrosion-resistant stainless steel

No angle in bath chamber, easy to clean

Uniquely designed heating method can up to 80 °C



### SPECIFICATIONS

Model	LTCHI11-6
Storage tank maximum capacity	5 L
Temperature range	-40-40°C
Ambient temperature range	+5-30°C
Temperature accuracy	±3°C
Cooling capacity at 20°C	1.95 Kw
Cooling capacity at 0°C	1.2 Kw
Cooling capacity at -20°C	0.65 Kw
Refrigerant	R404A
Security features	Delay, leakage, overcurrent, overvoltage
Total power	1750 W
Heating power	750 W
Power requirements	AC 220 V ± 10% /50 HZ
Pump flow max.	8 L/min
Maximum head	1.5 m
Inlet/Outlet pipe diameter	Φ16
Noise level	≤45
Liquid tank opening / depth	Φ220x180 mm
Dimensions	315Wx540Dx625H mm



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)