

RECIRCULATING CHILLER WATER COOLED LTCHI9-15



RECIRCULATING CHILLER WATER COOLED

LTCHI9-15

Also known as Laboratory Water Chiller.

LTCHI9-15 RECIRCULATING CHILLER WATER COOLED

The well-known product spleen compressor, high-efficiency shell and tube condenser, evaporator combination, super refrigeration, power saving PID microcomputer full-function control, easy to operate, can accurately control the water temperature within 3°C~35°C.

Unique new design stainless steel opening Type thermal insulation water tank, easy to clean and repair, reasonable internal pipeline layout, effectively reducing energy consumption.

Copper pipes are welded with Smick L30345% silver electrode, with high density and long life.

With current overload protection, high and low voltage switch, delay protection, over temperature protection, antifreeze, abnormal indication system.



SPECIFICATIONS

Model	LTCHI9-15
Freezing capacity	
kw	117.5 kw
kcal/h	101050 kcal/h
btu/h	400910 btu/h
Compressor	
Output power	30 kw
hp	20x2 hp
Weight	20 kg
Refrigerant	
Control mode	Thermostatic expansion valve
Type	R22 (R407C optional)
Evaporator(Type)	Tube-in-shell
Condensor(Water Chiller)	
Type	Tube-in-shell
Cooling water flow	500
In/out pipe	3 inch
Water tank capacity	330 L
Pump	
Type	Stainless steel centrifugal pump
Power kw	3.75 kw
Flow rate	367 l/min
Working pressure	3 bar
Chilled wateroutlet	3 inch
Pipe coupling	

Chilled water inlet	3 inch
Water tank drainage port	1 inch
Dimension(LXWXH) mm	2870x1055x1740 mm
Weight	1160 kg
Power	3 ph-380 V/50 Hz (220 V/400 V/415 V/440 V 50 Hz/60 Hz)
Temperature	5-35 °C
Tolerance	± 0.5 °C (± 1 °C at low load)
Safety protections	High and low pressure controller/anti-freezing switch/overload of pump and compressor protection/overheat protection/delayed protection



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com