

CLIMATE CHAMBER LTCHM20-7



CLIMATE CHAMBER LTCHM20-7

LTCHM20-7 CLIMATE CHAMBER

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

Microprocessor controller for temperature and humidity ensures of precise and reliable control

Imported compressor

Independent temperature-limiting alarm system ensures experiments run safely

Printer connector and RS485 connector are options which can connect printer and computer to record the parameters and the variations of temperature

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement



SPECIFICATIONS

| Model | LTCHM20-7 |
|------------------------|--|
| Capacity | 150 L |
| Temperature Range | 10-70°C |
| Display Resolution | 0.1°C |
| Temperature Stability | High $\pm 0.5^{\circ}\text{C}$ Low $\pm 1^{\circ}\text{C}$ |
| Temperature Uniformity | $\pm 2^{\circ}\text{C}$ |
| Humidity Range | 40-95% |
| Power Consumption | 2100 W |
| Ambient Temperature | +5 - 35°C |
| Electrical Requirement | 220 V 50 Hz |
| Interior Dimension | 550Wx405Dx670H mm |
| Exterior Dimension | 690Wx800Dx1430H mm |
| Shelves | 3 pcs |



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com