

# TEMPERATURE HUMIDITY STABILITY CHAMBER LTCHM22-13



# TEMPERATURE HUMIDITY STABILITY CHAMBER

## LTCHM22-13

### LTCHM22-13 TEMPERATURE HUMIDITY STABILITY CHAMBER

Microprocessor control, stainless steel chamber, semicircular arcs at corners for easy cleaning

Even air circulating system

R134a refrigerant, 2 imported compressors and fan motor

Over temperature and temperature difference alarms

Imported humidity sensor which can be used in high humidity environment

Balance temperature and humidity adjusting system

There is a 25mm instruction connection hole on the left side of the chamber for easy testing operation and temperature measurement

UV light system for periodic sterilization of chamber.(Option)

Independent audible and visible temperature-limiting alarm system ensures experiments run safely

RS485 connector can connect computer record and inspect the parameters and the variations of temperature



### SPECIFICATIONS

Model	LTCHM22-13
Capacity	400 L
Temperature Range	0-65°C without illumination
Temperature Stability	±0.5°C
Temperature Uniformity	±2°C
Illumination	0-6000LX adjustable
Illumination difference	≤±500LX
Timing Range	1-99 hours each period
Humidity and temp adjusting	Balance temperature adjusting
Cooling system/cooling mode	Two sets of imported compressor work rotationally
Controller	Programmable(LCD screen)
Sensor	Temp: Pt100
Ambient Temperature	RT+5-30°C
Electrical Requirement	AC 220 V 50 Hz
Power Consumption	3200 W
Interior Dimension	700Wx550Dx1140H mm
External Dimension	950Wx850Dx1850H mm
Shelves	4 pcs
Safety Device	Compressor overheating and overpressure protection, Fan overheating protection Over temperature protection, Overload protection, Water protections
Remark	intensity of illumination detector.



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)