

# PLANT GROWTH CHAMBER LTCHM26-6



# PLANT GROWTH CHAMBER LTCHM26-6

## LTCHM26-6 PLANT GROWTH CHAMBER

Microprocessor controller for temperature and humidity and light intensity, 30 programs

Large LCD screen

Simulate changing temperature and light in day/night

Polished stainless-steel chamber, semicircular arcs at corners for easy cleaning, and the space between the shelves in the chamber is adjustable

R134a refrigerant, two imported compressors, continuous running time

Independent temperature-limiting alarm system ensures experiments run safely

RS485 connector is option which can connect computer to record the parameters and the variations of temperature

### SPECIFICATIONS

Model	LTCHM26-6
Capacity	800 L
Display Resolution	0.1°C
Temperature Range	Without Lighting: 0-50°C , With lighting: 10-50°C
Temperature Stability	±1°C
Temperature Uniformity	±2°C
Lighting Type	Shelves illumination(two Shelves)
Programmer Function	Temperature, humidity, light intensity, can be set separately, and 30 programmers Time range is 1-99 hours 59mins for each programmer
Power Consumption	3700 W
Electrical Requirement	380 V 50 HZ
Ambient Temperature	RT+5-30°C
Interior Dimension	800Wx590Dx1650H mm
ExteriorDimension	1475Wx890Dx1780H mm
Shelves	3 pcs



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)