

UV TEST CHAMBER LTCHM28-1



UV TEST CHAMBER LTCHM28-1

LTCHM28-1 UV TEST CHAMBER

4.3 inch touch screen, menu type interface could set parameters fast, which is easy to understand and operation.

BPT sensor, cabinet temperature and rain cycle etc, which can be visually setting and displaying

With 4 pieces of 20W ultraviolet lamp, more stable and the life of the lamp is up to 5000 hours

B-UV-S series provide 3 spray headers which can meet the uniformity of rainfall for flat sample rack

Radiation intensity adjustment with optional RM-20 irradiance meter which by manual adjustment

Blackboard temperature self-control by test set value, to meet user for lighting, condensation, spray, temperature and other aging test chamber

Build-in 4 pieces of 70x150 flat sample racks, the users can test for three-dimensional or flat samples



SPECIFICATIONS

Model	LTCHM28-1
Light cycle	45°C-80°C
Condensation cycle	45°C-60°C
Type	UVA
Power	20W/pc, total 4 pcs
Wavelength range	Standard with UVA@340nm
Irradiance	Handle
Calibration function	No
Spraying function	3-hole spraying
Sample shelf size	8 pcs standard sample test shelf
Center distance between sample and lamp	150mm-280mm
Exterior dimension	770Wx565Dx690H mm
Cycle mode	Dark, light, spray, condensate set multi-cycle automatic control
Light control	Handle
Electrical Requirement	220 V 50 Hz
Power Consumption	2000 W



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com