ILLUMINATING CLIMATE CHAMBER LTCHM9-2



ILLUMINATING CLIMATE CHAMBER LTCHM9-2

Used in Supports plant and insect growth, tissue cultivation, antibiotic cultivation and preservation and other controlled temperature experiments..

Also known as Humidity Chamber, Laboratory Climatic Chamber.

LTCHM9-2 ILLUMINATING CLIMATE CHAMBER

Forced convection mode

30 Stages programmable Micocomputer PID

Imported environmental protection insulation materials

Excellent Imported temperature and humidity Sensor

SUS304 stainless steel interior material ALLCOLDTM: Refrigeration Technology ALLIGENTTM: Humidification System ALLFLOWTM: Perfect Air Current Cycling



SPECIFICATIONS

Model	LTCHM9-2
Capacity	300 L
Temperature Range	10°C~65°C(Light on)/0°C~60°C(Light off)
Temperature Uniformity	±1 (10-40°C)
Temperature Fluctuation	±1°C
Temperature Resolution	0.1°C
Using Environment Temperature	Ambient temp.10~30°C
Using Environment Humidity	<70%
Illumination Range	0-15000 (5 stages adjustable)
Timer Range	0-99h/0-9999mins
Shelves	4
Inner Dimension	1100 x 540 x 520 mm
Overall Dimension	1780 x 770 x 815 mm
Weight (Net/Gross)	183 kg
Power	1350 W



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com