

# HAND-HELD CHEMICAL IDENTIFIER LTCIA10-1



# HAND-HELD CHEMICAL IDENTIFIER LTCIA10-1

## LTCIA10-1 HAND-HELD CHEMICAL IDENTIFIER

High accurate and flexible identification of a wide range of the unknown substance with extensible substance library

High speed inspection

no warm up time. It can directly detect once turn on

Handheld and ergonomic design

Non-destructive and Non-radioactive testing

Analyze and identify substances in several seconds typically

Micro USB2.0 and Wi-Fi for data transfer and software update

Can check the information from mobile phone software

Integrated Bluetooth for data sending

Friendly operation based on touch-screen with graphical user interface and minimal training required Virtual keyboard: Built-in Win8.1 system, a virtual keyboard operation, easy to input



## SPECIFICATIONS

Model	LTCIA10-1
Explosives	TNT ,RDX, PETN, Octagon, Sulfur and Ammonium Nitrate, etc.
Narcotics	Cocaine,hydrochloride, Palavering hydrochloride, Methamphetamine (meth), Methamphetamine and Ketamine hydrochloride (K), etc.
Liquid Threats	Acetic acid, Acetic anhydride, Ethanol, Chloroform, Methanol, Toluene, Acetone, Pyridine, Benzene, Ethyl ether, Cyclohexane, 1-2 Dichloroethane, Xylene, N,N-dimethylformamide, Isoamyl alcohol, Isopropyl alcohol, Nitrobenzene, Cyclohexanone, Isoamyl acetate, Tetrahydrofuran, etc
Others	infinitely extension database
Spectrum range	200 – 3900 cm <sup>-1</sup>
Resolution	8 – 10 cm <sup>-1</sup>
Laser wavelength	785 nm
Laser security classification	3 B
Detector	Backside highly-sensitive CCD detector
Laser consumption	0-500mW adjustment
Integral Time	100 ms- 5s
Analysis Time	3 s
Alarm	Audio and visual alarm. And show you test result
Detection Way	Acquiring a usable signal a few millimetres away from the sample
Probe working focal length	8 mm
Warm up time	No
Working temperature	0°C to 40°C
Working humidity	≤93%
Storage temperature	-20°C to 55°C
Storage humidity	≤80%
Data	By USB or wireless to import or export
Data storage	Save 300,000 records
Battery	Rechargeable 4 hours lithium battery

Dimension (LxWxH)	160x222x74 mm
Weight	2.3 kg
Power	12V/3A adaptor



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)