

-10°C TO -25°C FREEZER UPRIGHT LTFRE18-2



-10°C TO -25°C FREEZER UPRIGHT LTFRE18-2

LTFRE18-2 -10°C TO -25°C FREEZER UPRIGHT

Chemically stable, CFC-Free, environmentally, safe refrigerant

High density CFC-Free urethane foam insulation for rigidity and stable storage temperature

Microprocessor control, digital display adjustable

LED digital display

Audible and visible alarm

Controller password protect function to avoid change running parameter randomly

Independent inner door to avoid more cooling leaking out, and provide more stable internal temperature performance

Upright side door with built-in handle for easy-opening; limit door hinge to prevent collision when door open

Lockable caster design for customer to move as needed



SPECIFICATIONS

Model	LTFRE18-2
Capacity	485 L
Temperature Range	-10°C to -25°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	HC-R290
Internal Dimension	1455x525x665 mm
Overall Dimension	1655x755x915 mm
Package Size	1710x885x1020 mm
Exterior	Color Sprayed steel
Controller	Microprocessor, Digital display
Sensor	NTC
Compressor Brand/QTY	CUBIGELN/1
Alarm	High/low temperature, Power off, Sensor malfunction, Temperature controller malfunction
Standard Accessories	Caster Optional accessories: Test hole
Weight (Net/Gross)	124 / 138 kg
Rated Power	295 W
Power Consumption (Kwh/24hrs)	3.45
Power Supply	220V, 50Hz



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com