-10°C TO -40°C ULTRA LOW TEMPERATURE FREEZER UPRIGHT LTFRE22-2



-10°C TO -40°C ULTRA LOW TEMPERATURE FREEZER UPRIGHT LTFRE22-2

LTFRE22-2 -10°C TO -40°C ULTRA LOW TEMPERATURE FREEZER UPRIGHT

LED digital display and increment at 0.1°C

Permanently lubricated cooling fan for safety and longevity

Independent inner door to avoid more cooling leaking out, and provide more stable inside temperature performance

High density CFC-Free urethane foam insulation

Build-in lock with safety

Lockable caster design

Chemically stable, CFC -free, commercially available and environmentally safe refrigerant

Optimized refrigeration system designed to maximize cooling effect and temperature uniformity

Visible and Audible alarm

Corrosion proof cabinet interior design

Power failure protect: the device would be attack by the high current when all devices restart simultaneously, the start-delay function would protect device from the damage



SPECIFICATIONS

Model	LTFRE22-2
Capacity	268 L
Temperature Range	-30°C to -40°C
Ambient Temperature	10°C ~ +32°C
Defrosting	Manual
Cooling Type	Direct Cooling
Insulation Material	PURF
Refrigerant	R290
Internal Dimension	508x455x1137 mm
Overall Dimension	673x676x1630 mm
Package Size	770x770x1804 mm
Drawers/Shelves	Shelves
Interior	Color sprayed steel
Exterior	Color sprayed steel
Controller	Microprocessor, Digital display
Sensor	NTC
Compressor Brand/QTY	CUBIGEL/1
Condenser	Wire tube
Noise Level	48 db
Alarm	High/low temperature, Power off, Sensor malfunction, Temperature controller malfunction
Standard Accessories	Caster

Optional Accessories	Test hole
Weight (Net/Gross)	98.5/115 kg
Rated Power	300 W
Power Consumption (Kwh/24hrs)	4
Rated Current A	1.6 A
Power Supply	220 V, 50 Hz



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com