-10°C TO -86°C ULTRA LOW TEMPERATURE FREEZER UPRIGHT LTFRE27-15



-10°C TO -86°C ULTRA LOW TEMPERATURE FREEZER UPRIGHT LTFRE27-15

LTFRE27-15 -10°C TO -86°C ULTRA LOW TEMPERATURE FREEZER UPRIGHT

Settable high temperature and low temperature alarms

Automatic clean-filter alarm and sensor error alert

Adjustable storage shelf height

Unique insulated inner door design for four separate storage compartments to minimize frost buildup inside the chamber

Specialized control system design for a well-balanced operation of cascade refrigeration system

Audible and visible alarm

Door open feature standard and USB port for temperature date downloading standard on upright models

Remote alarm contacts

Unique door seal design for the minimum loss of cold temperature during a door opening

High performance VIP insulation panels to minimize cabinet heat gain and to improve temperature stability



SPECIFICATIONS

| Model | LTFRE27-15 |
|------------------------|---------------------------------|
| Capacity | 838 L |
| Temperature Range | -40°C to -86°C |
| Ambient Temperature | 10°C ~ +32°C |
| Temperature Increament | 1°C |
| Defrosting | Manual |
| Cooling Type | Direct Cooling |
| Insulation Material | PURF |
| Refrigerant | Mixed-gas |
| Internal Dimension | 894x718x1310 mm |
| Overall Dimension | 1179x1135x1994.5 mm |
| Package Size | 1212x1098x2185 mm |
| Drawers/Shelves | Stainless steel shelf/3 |
| Interior | Stainless steel |
| Exterior | Color sprayed steel |
| Controller | Microprocessor, Digital display |
| Sensor | PTC |
| Compressor Brand/QTY | SECOP/2 |
| Evaporator | Submerged coil evaporator |
| Evaporator Material | Copper tube evaporator |
| Condenser | Copper tube and finned |

| Alarm | High/low temperature, Power off, Sensor malfunction, Abnormal voltage, Filter screen check, Thermostat failure, Low battery, Condensor clean, High ambient temperature, Door ajar |
|---------------------------------|--|
| Standard Accessories | Castor, Inner doorx2, Test hole 1/25 mm, USB port |
| Optional Accessories | Data logger, CO2 backup system, LN2 backup system, Temperature recorder, Storage racks and storage box |
| Weight (Net/Gross) | 391 / 424 kg |
| Rated Power | 840 W |
| Power Consumption (Kwh/24hrs) | 14.25 |
| Rated Current A | 6.5 |
| Power Supply | 220V, 50Hz |



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com