

DUCTLESS FUME HOOD LTFUM11-3



DUCTLESS FUME HOOD LTFUM11-3

Used in Forensics, Life Sciences, Clinical, Research Field.

Also known as Carbon-filtered enclosures, Filtered fume hoods.

LTFUM11-3 DUCTLESS FUME HOOD

LCD Touch screen control panel, easy to operate.

With memory function in case of power-failure.

8°slope front ergonomics design, fatigue-free working posture.

Temperature and humidity sensors, can detect indoor temperature and humidity.

Three side transparent Acrylic windows, front window reversal design, easy to operate.

Double-layers structure: 1mm sheet metal surface; Chemical resistant phenolic resin work table.

Electronic control system, anti-overload, anti-electric shock, stable performance, long service life.

Inside and outside probe, detect indoor air pollution and filter conditions. Audible and visual alarm for changing filter.



SPECIFICATIONS

Model	LTFUM11-3
Air Velocity	0.4~0.6 m/s
Airflow Volume	432m ³ /h
Max.Opening	650mm
Work Surface Height	900mm
Blower	Built-in centrifugal blower, speed adjustable
Front Window	Acrylic window; Manual; Reversal design
Exterior Material	Cold-rolled steel with anti-bacteria powder coating
Side Window Material	Acrylic Window
Work Table Material	Chemical resistant phenolic resin
Chemical Filter	4 pcs
UV Lamp(optional)	Emission of 253.7 nanometers for most efficient decontamination
Fluorescent Lamp	14Wx3
Standard Accessories	Fluorescent Lamp, Base cabinet, Total load of 2 waterproof sockets: 500W;Chemical Filter
Optional Accessory	Water tap, Gas tap, Water sink, Electric height, Adjustable base stand, HEPA Filter, USB module,UV Lamp
Internal Size (WxDxH)	1410x690x740mm
External Size (WxDxH)	1500x940x2140mm
Main Body Package Size	1650x1110x1490mm
Package Size (Base Cabinet)	1650x1110x1060mm
Gross Weight	380kg
Consumption	500 W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com