

STANDARD FUME HOOD LTFUM8-5



STANDARD FUME HOOD LTFUM8-5

Used in Metal analysis, Pharmacy, Research Field, Commercial, Medical, Laboratory.
Also known as Standard Fume Hood, Laboratory Fume Hood, Chemical Fume Hood.

LTFUM8-5 STANDARD FUME HOOD

Interior body includes melamine board with acid and alkali resistance function

LCD display

Exterior body is of cold-roll steel with anti-bacterial powder

Working chamber is made of solid chemical-resistant material

UV lamp to sterilize the working area

Adjustable air velocity with electrical controlled glass

Adjustable blower speed of a centrifugal fan



SPECIFICATIONS

Model	LTFUM8-5
Air Velocity	0.3~0.8 m/s
Max Opening	520 mm
Work Surface Height	750 mm
System Exhaust Volume	630m ³ /h
Front Window	Motorized, 5 mm toughened glass; Anti-UV Exterior Body: cold rolled steel with anti-bacteria powder coating.
Work Table Material	Chemical resistant Phenolic resin
LED Lamp	8Wx 1
UV Lamp	20 W Emission of 253.7 nanometers for most efficient decontamination
Blower	Built-in centrifugal blower, Speed adjustable with 9 levels
Standard Accessory	Water tap, Gas tap, Water sink, base stand, UV lampx2, LED lamp, Socket, 4.3 meters exhaust duct, Active carbon filter, foot switch, Waterproof Socket- 1 pc
Optional Accessory	HEPA filter
Internal Size (WxDxH)	880x730x745mm
External Size (WxDxH)	1000x840x2150mm
Package (Main Body)	1150x1120x1680 mm
Noise Level	≤60 dB
Gross Weight	230 kg
Consumption	400 W
Power Supply	AC220V±10%, 50/60Hz 110V+10%, 60Hz

ACCESSORIES

Accessory Code	Name
6200812008	Fluorescent lamp

Accessory Code	Name
6200808009	Gas tap

6200812009	UV lamp
6200812010	Base stand
6200812011	Waterproof socket
6200808008	water tap

6200808010	Water sink
6200812012	4 meters PVC exhaust duct
6200808014	Active carbon filter
6200812013	Foot switch



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com