SEMI AUTOMATIC CRYOSTAT LTHIS8-3



SEMI AUTOMATIC CRYOSTAT LTHIS8-3

Used in Tissue biopsy, Slice tissue slide, Magnetic Resonance Imaging (MRI), Pathological diagnosis, Analysis and Research in Hospital and Medical colleges..

Also known as Ultrafine "deli-slicer".

LTHIS8-3 SEMI AUTOMATIC CRYOSTAT

Adjustable cool plate temperature with -45°C minimum. Super large, may hold 28 chucks at meantime. New designed hammer make the tissues platter than the traditional one. Adjustable temperature with -50 °C minimum. Cutting angle is12°universally adjustable to meet varieties of needs. Retraction function to avoid scratches on specimen. Freezing chamber adjustable temperature with - 40 °C minimum. The handwheel can be locked at any position. Injection moulding shell with mild feeling is durable and easy to clean. 40 decibel silent freezing system with duel compressors made in Germany. Blade holder auto pump-blade device may avoid incised wound. Anti-fog glass window.



SPECIFICATIONS

| Model | LTHIS8-3 |
|---|---|
| Freezing chamber temperature range | - 40 °C \sim -10 °C |
| Freezing shelf minimum temperature | - 45 ℃ |
| Chuck holder minimum temperature | - 50 ℃ |
| Minimum temperature of Peltier element on freezing shelf | - 60 °C |
| Number of Peltier element cooling spot | 2 |
| Maximum specimen size | 50×80 mm |
| Chuck hold maximum adjustable angle | 12 ° |
| Specimen vertical stroke | 70 mm |
| Specimen horizontal stroke | 20 mm |
| Rough feeding speed | (0.9 mm/s; 0.3 mm/s) |
| Section thickness range 1 μ m \sim 100 μ m adjustable | 1 $\mu m \sim~20~\mu m$, in 1 μm increments |
| Section thickness range 1 $\mu m \sim 100 \ \mu m$ adjustable | 50 μm \sim 100 μm, in 5 μm increments. |
| Trimming thickness range 10 μ m \sim 400 μ m adjustable | 50 $\mu m \sim~100~\mu m$, in 10 μm increments |
| Trimming thickness range 10 μ m $\sim 400 ~\mu$ m adjustable | 100 μm $\sim $ 400 μm, in 50 μm increments |
| Retraction range $0\mu m\sim 80\mu m$ adjustable, in $5\mu m$ increment | 0 μm $\sim~$ 80 μm adjustable, in 5 μm increment |
| Voltage and frequency | AC 220 V \pm 10 %, 50 Hz (Standard) or AC 110 V \pm 10 %, 60 Hz |
| Power | 800 W |
| Net weight | 125 kg |
| Dimensions(W×D×H) | 660×640×1130 mm |

labtare.com

2



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com