

# HORIZONTAL LAMINAR AIR FLOW LTLAM10-1



# HORIZONTAL LAMINAR AIR FLOW LTLAM10-1

Used in Bioscience, Food processing, Pharmaceuticals, Aerospace, Medical research Laboratories, Hospitals, Research. Also known as Minimal-Turbulence Air Flow, Laboratory Laminar Flow, Clean Bench, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Tissue Culture Hood, Laminar Air Flow Cabinet, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

## LTLAM10-1 HORIZONTAL LAMINAR AIR FLOW

ETL certification, Satisfy North American market.

With memory function in case of power-failure.

Audio and visual alarm (Abnormal airflow velocity).



## SPECIFICATIONS

Model	LTLAM10-1
AirFlow Velocity	80~99fpm
HEPA Filter	One,99.995% efficiency at 0.3um
Pre filter	Polyster fibre, Washable
Work Surface Height	750 mm
Main Body Material	1.0 mm Cold-rolled steel with anti-bacteria powder coating.
Work Table Material	304 Stainless steel
Front Window	5 mm toughened glass, anti-UV.
LED Lamp	14Wx1
Display	LCD display
Waterproof Socket	One socket (Double type), America standard, Max.Power: 500W
Standard Accessory	Manually height adjustable base stand,LED lamp, wind speed sensor, waterproof socket , Stainless Steel LV.Bar with 10 hooks
Optional Accessory	UV lamp
Noise	268dB(A)
External Size	1100x810x (1720-1980)mm
Internal Size	1000Wx500Dx600H mm
Package Size	1240Wx1090Dx1250H mm
Gross Weight	190kg
Consumption	950W
Power Supply	103.5-126.5V, 60Hz, 10A

## ACCESSORIES

Accessory Code	Name
6200812008	Fluorescent lamp
6200812009	UV lamp
6200812010	Base stand
6200812011	Waterproof socket



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)