

HORIZONTAL LAMINAR AIR FLOW LTLAM10-2



HORIZONTAL LAMINAR AIR FLOW LTLAM10-2

Used in Bioscience, Food processing, Pharmaceuticals, Aerospace, Medical research Laboratories, Hospitals, Research. Also known as Minimal-Turbulence Air Flow, Laboratory Laminar Flow, Clean Bench, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Tissue Culture Hood, Laminar Air Flow Cabinet, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LTLAM10-2 HORIZONTAL LAMINAR AIR FLOW

ETL certification, Satisfy North American market.

With memory function in case of power-failure.

Audio and visual alarm (Abnormal airflow velocity).



SPECIFICATIONS

Model	LTLAM10-2
AirFlow Velocity	80~99fpm
HEPA Filter	One,99.995% efficiency at 0.3um
Pre filter	Polyster fibre, Washable
Work Surface Height	750 mm
Main Body Material	1.0 mm Cold-rolled steel with anti-bacteria powder coating.
Work Table Material	304 Stainless steel
Front Window	5 mm toughened glass, anti-UV.
Display	LCD display
Waterproof Socket	One socket (Double type), America standard, Max.Power: 500W
LED Lamp	18Wx1
Standard Accessory	Manually height adjustable base stand,LED lamp, wind speed sensor, waterproof socket , Stainless Steel LV.Bar with 10 hooks
Optional Accessory	UV lamp
Noise	268dB(A)
External Size	1500x810x (1720~1980)mm
Internal Size	1400Wx500Dx600H mm
Package Size	1640Wx1090Dx1250H mm
Gross Weight	265kg
Consumption	950W
Power Supply	103.5-126.5V, 60Hz, 10A

ACCESSORIES

Accessory Code	Name
6200812008	Fluorescent lamp
6200812009	UV lamp
6200812010	Base stand
6200812011	Waterproof socket



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com