

HORIZONTAL LAMINAR AIR FLOW LTLAM10-4



HORIZONTAL LAMINAR AIR FLOW LTLAM10-4

Used in Bioscience, Food processing, Pharmaceuticals, Aerospace, Medical research Laboratories, Hospitals, Research. Also known as Minimal-Turbulence Air Flow, Laboratory Laminar Flow, Clean Bench, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Tissue Culture Hood, Laminar Air Flow Cabinet, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LTLAM10-4 HORIZONTAL LAMINAR AIR FLOW

ETL certification, Satisfy North American market.

With memory function in case of power-failure.

Audio and visual alarm (Abnormal airflow velocity).



SPECIFICATIONS

Model	LTLAM10-4
Type	Horizontal Laminar Flow
Air Flow Velocity	80~99fpm
HEPA Filter	One,99.995% efficiency at 0.3um
Pre-filter	Polyester fiber, washable
Work Surface Height	750mm
Main Body Material	1.0 mm Cold-rolled steel with anti-bacteria powder coating.
Work Table Material	304 stainless steel
Front Window	5 mm toughened glass, anti-UV.
LED Lamp	22W x1
Display	LCD display
Max Opening	430 mm
Waterproof Socket	Two, total load ≤500W
Standard Accessory	LED lamp, UV lamp x2, Base stand, Gas Tap, Waterproof socket x2, Water Tap
Optional Accessory	Electric height adjustable base stand
Internal Size	1700Wx500Dx570H mm
External Size	1800Wx820Dx2070H mm
Package Size	1950Wx1060Dx1600H mm
Gross Weight	328kg
Noise	<65dB
Consumption	500W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%, 60Hz

ACCESSORIES

Accessory Code	Name
3001011008	Fluorescent lamp
3001011009	Gas tap
3001011010	Total load of two waterproof sockets: 500W
3000810008	UV Lampx2
3001011011	Base Stand
3001011012	Water Tap



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com