

VERTICAL LAMINAR AIR FLOW LTLAM12-1



VERTICAL LAMINAR AIR FLOW LTLAM12-1

Used in Electronic sectors, Industrial sectors, Medical, Pharmaceutical, Healthcare.

Also known as Tissue Culture Hood, Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LTLAM12-1 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers



SPECIFICATIONS

| | |
|---------------------|---|
| Model | LTLAM12-1 |
| Type | Vertical Laminar Flow |
| Air Flow Velocity | Average of 0.3~0.5m/s, air speed adjustable. |
| HEPA Filter | 99.995% efficiency at 0.3 μ m |
| Pre-filter | Polyester fiber, washable |
| Work Surface Height | / |
| Max Opening | / |
| Front Window | / |
| UV Lamp | 15Wx1 Emission of 253.7 nanometers |
| illuminating Lamp | Fluorescent lamp 8W*1 |
| Display | LED Display |
| Main Body Material | Cold-rolled steel with anti-bacteria powder coating |
| Work Table Material | 304 stainless steel |
| Caster | / |
| Standard Accessory | Fluorescent lamp; UV lamp x2; Water & gas tap. |
| Optional Accessory | / |
| Noise | <65dB |
| Internal Size | 630Wx375Dx615H mm |
| External Size | 680Wx410Dx1160 mm |
| Package Size | 840Wx560Dx1380H mm |
| Gross Weight | 50kg |
| Consumption | 160W |
| Power Supply | AC220V \pm 10%, 50/60 Hz; 110V \pm 10%, 60Hz |



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com