

VERTICAL LAMINAR AIR FLOW LTLAM12-3



VERTICAL LAMINAR AIR FLOW LTLAM12-3

Used in Electronic sectors, Industrial sectors, Medical, Pharmaceutical, Healthcare.

Also known as Tissue Culture Hood, Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LTLAM12-3 VERTICAL LAMINAR AIR FLOW

Microprocessor controller

Pre-filter: Polyester fiber, washable

UV Lamp: Emission of 253.7 nanometers



SPECIFICATIONS

Model	LTLAM12-3
Type	Vertical Laminar Flow
Air Flow Velocity	Average of 0.3~0.45m/s, air speed adjustable.
HEPA Filter	99.995% efficiency at 0.3 μ m
Pre-filter	Polyester fiber, washable
Work Surface Height	750mm
Max Opening	400mm
Front Window	Manual, 5mm toughened glass, anti-UV
UV Lamp	20Wx1 Emission of 253.7 nanometers
illuminating Lamp	LED lamp 12W*1
Display	LCD Display
Main Body Material	Cold-rolled steel with anti-bacteria powder coating
Work Table Material	304 stainless steel
Caster	Universal wheel with leveling feet
Standard Accessory	LED lamp; UV lamp x2; Base stand.
Optional Accessory	Electric height adjustable base stand
Noise	<65dB
Internal Size	935Wx530Dx650H mm
External Size	1060Wx620Dx1850 mm
Package Size	1240Wx900Dx1350H mm
Gross Weight	185kg
Consumption	150W
Power Supply	AC220V \pm 10%, 50/60 Hz; 110V \pm 10%, 60Hz



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com