

VERTICAL LAMINAR AIR FLOW LTLAM13-3



VERTICAL LAMINAR AIR FLOW LTLAM13-3

Used in Pharmaceutical, Pathology lab, Life science research, Plant tissue and cell culture.

Also known as Laminar Air Flow Cabinet, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Laminar Flow Cabinet.

LTLAM13-3 VERTICAL LAMINAR AIR FLOW

ETL certified, Satisfy North American market.

With memory function in case of power-failure.

Audio and visual alarm(Abnormal airflow velocity).

Interlock function: UV Lamp and blower LED Lamp.



SPECIFICATIONS

Model	LTLAM13-3
Type	The ETL certified vertical laminar flow cabinet
Airflow Velocity	Average of 80~99 fpm
HEPA Filter	One,99.995% efficiency at 0.3 μ m
Pre-Filter	Polyester fiber
Work Surface Height	750~1010mm
Max Opening	480mm
Working area Material	304 stainless steel
Main Body Material	1.2mm Cold-rolled steel with anti-bacteria powder coating.
Front Window Material	Motorized, 5mm toughened glass, anti-UV
Waterproof Sockets	One socket (Double type), America standard, Max.Power: 500W
UV Lamp	18W x1
LED Lamp	10W x1
Display	LCD Display
Illumination	\geq 300lx
Noise	\leq 68dB(A)
Standard Accessory	Manually height adjustable base stand; LED lamp; UV lamp; Wind speed sensor; Waterproof socket.
Internal Size	700Wx575Dx625H mm
External Size	800x700x(2090~2340)mm
Package Size	940Wx970Dx1560H mm
Gross Weight	190kg
Consumption	750W
Power Supply	110V \pm 10%V, 60HZ



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com