

COMPOUNDING HOOD HEPA FILTERED ENCLOSURE LTLAM14-5



COMPOUNDING HOOD HEPA FILTERED ENCLOSURE LTLAM14-5

Used in Research, Pharmaceutical, Medical, Manufacturing areas, Electronic setors, Industrial sectors, Laboratory, Healthcare.

Also known as Desktop Laminar Air flow, Benchtop Laminar Air Flow, Laminar Flow Cabinet, Clean Bench, Laboratory Laminar Flow, Laboratory Laminar Air Flow, Tissue Culture Hood, Laminar Air Flow Cabinet, Minimal-Turbulence Air Flow, Laminar Flow Cabinet, Laminar Flow Hood, Laminar Flow.

LTLAM14-5 COMPOUNDING HOOD HEPA FILTERED ENCLOSURE



SPECIFICATIONS

| | |
|---------------------|---|
| Model | LTLAM14-5 |
| Type | Desktop Laminar Flow |
| Airflow Velocity | 0.3~0.8m/s |
| Filter | Active Carbon Filter, HEPA Filter |
| Max Opening | 660mm |
| Main Body Material | Cold-rolled steel with anti-bacteria power coating |
| Work Table Material | Solid physicochemical steel plate |
| Front Window | Manual, acrylic material |
| UV Lamp | 15W x1 Emission of 253.7 nanometers |
| LED Lamp | 12W x1 |
| Display | LED Display |
| Noise | ≤60dB |
| Standard Accessory | Active carbon filter, HEPA filter, LED lamp x1, 4 meters PVC exhaust duct, Diameter: 250mm. |
| Optional Accessory | Base stand, UV lamp x2 |
| Internal Size | 940Wx550Dx700H mm |
| External Size | 1000Wx620Dx1150H mm |
| Package Size | 1140Wx740Dx1340H mm |
| Gross Weight | 145kg |
| Consumption | 200W |

Power Supply

AC220V±10%, 50/60Hz; 110V±10%, 60Hz



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com