

MICROWAVE DIGESTION SYSTEM LTMDG8-14



MICROWAVE DIGESTION SYSTEM LTMDG8-14

Used in Pharmaceutical Analysis, Agricultural, Environmental Analysis, Biological Sciences.

Also known as Microwave Digester, Microwave Extraction.

LTMDG8-14 MICROWAVE DIGESTION SYSTEM

Anti-corrosion design: TEFLON coating on the surface, acid/alkali proof.

Heating uniform and fast: Adopt graphite block (antioxidant), heating faster and energy transfer faster, temperature between holes more uniform.

Safety protection: adopt unique air duct insulation tech, keep the temperature ultralow, protect operator



SPECIFICATIONS

Model	LTMDG8-14
Temperature Range	RT +5 ± 450 °C
Temperature Accuracy	±1 °C (450 °C)
Heating Method	Infrared heating and high-purity graphite conduction
Heating Insulation Method	Unique air duct insulation technology
Digestion Tube Capacity	300ml
Max.Capacity	20pcs/batch
Power Supply	AC220V±10%,50Hz
Power Consumption	3600W
External Size(WxDxH)	515x458x730 mm
Package Size(WxDxH)	890x600x630 mm
Gross Weight	57kg



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com