

MICROWAVE DIGESTION SYSTEM LTMDG8-15



MICROWAVE DIGESTION SYSTEM LTMDG8-15

Used in Pharmaceutical Analysis, Agricultural, Environmental Analysis, Biological Sciences.

Also known as Microwave Digester, Microwave Extraction.

LTMDG8-15 MICROWAVE DIGESTION SYSTEM

The temperature in the furnace is continuously adjustable, the temperature is constant, and the instrument is easy to operate.

The surface of the whole machine is sprayed with Teflon, which is resistant to strong acid and alkali corrosion, and

protects the safety of experimenters and equipment.

Heating element detection technology, automatic alarm prompt for abnormal situation.

The whole machine has multiple protections such as overvoltage, overcurrent and overheating.

The heat conduction efficiency is high and all parts of the sample are heated evenly, which prevents the loss of heat to the greatest extent.



SPECIFICATIONS

Model	LTMDG8-15
Vessel Quantity	12pcs
Accuracy	±1 °C
Maximum Working Temperature	240 °C
Hole Diameter	39.5 mm
Hole Depth	107 mm
Power	1500W
Power Supply	Standard: 220V 50Hz, optional: 110V 60Hz (external transformer)
Packing Size	535x420x345 mm
Gross Weight	26.2kg



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com