MICROWAVE DIGESTION SYSTEM LTMDG8-3



MICROWAVE DIGESTION SYSTEM LTMDG8-3

Used in Pharmaceutical Analysis, Agricultural, Environmental Analysis, Biological Sciences. Also known as Microwave Digester, Microwave Extraction.

LTMDG8-3 MICROWAVE DIGESTION SYSTEM

Compatible with 10 position rotor which meets different digestion demands.

Equip with 316L stainless explosion-proof cavity, coated with multilayer anticorrosive and heat resisting coatings, which greatly prolongs its service life and ensure the safety of operation.



SPECIFICATIONS

Model	LTMDG8-3		
Vessel Quantity	10		
Pressure Monitoring System	Contactless pressure sensors. All vessels scanning monitoring		
Working Pressure Range	0-6MPa		
Working Temperature Range	50-400 °C Accuracy: ±0.1 °C		
Vessel Volume	100mL		
Display	Smart 7 inch color touch screen		
Rotation	360° continuous rotation		
Microwave Power	0 ? 1000 W (Adjustable)		
Microwave Frequency	2450MHz		
Cavity Volume	35L		
Microwave Leakage	<5mw/cm2		
Power	AC 220V ± 10%,10A, 50/60Hz		
Dimension (LxWxH)	490x560x533 mm		
Weight	40 kg		

OPTIONAL ACCESSORIES

Accessory Code	Name	Sample quantity	Aperture and Hole depth	Temperature Control Range
7800810008	Heating Blocks	12	Ф 39x65mm	Room Temperature - 250°C



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com