

HAZE METER LTMET107-2



HAZE METER LTMET107-2

LTMET107-2 HAZE METER

Double standard ISO & ASTM
Easy to operate, faster and more accurate measurement
Dynamic measurement
With compensation port, so that the measurement data more accurate
Easy to measure and widely applicable to samples
Quality control software



SPECIFICATIONS

| Model | LTMET107-2 |
|----------------------------------|---|
| Optical Geometry | Transmittance: 0/D (parallel illumination, diffuse reflection receiving) |
| Standards compliant | ASTM D1003/1044,ISO 13468,ISO 14782,GB/T 2410,JF 1303-2011,CIE 15.2,JIS K7105,JIS K7361,JIS K 7136 |
| Integrating Sphere Size | Φ154mm |
| Illuminant | D65,A,C |
| Spectral mode | / |
| Sensor | The PD array detector satisfies CIE V(λ)2 degree visual response |
| Measurement Wavelength range | / |
| Wavelength Pitch | / |
| Semi-bandwidth | / |
| Measuring range of transmittance | 0-100% |
| Measurement Aperture | Φ20mm/Φ15mm/Φ8mm/Φ4mm(Select a single aperture) |
| Sample thickness | less than 170 mm |
| color space | / |
| Color Difference Formula | / |
| Other Colorimetric data | Haze(ASTM D1003/1044,ISO13468),Transmittance T(ISO),Transmittance T(ASTM) |
| Observer | 2° |
| Displayed Data | Pass/fail result |
| Measurement Time | About 1.5s |
| Measurement accuracy | 0.01 |
| Repeatability | Φ20 mm caliber, less than 0.08 (after the instrument is warmed up and corrected, test the standard deviation value of the standard haze sheet with a haze of about 30 is tested at an interval of 5s) |
| Inter-instrument agreement | Φ20mm,with 0.4 (After the instrument is preheated and calibrated, the standard deviation between the standard haze tablet and the reference value is tested at an interval of 5s.) |
| Operating Environment | 0~40°C (32~104°F) |
| Storage Environment | -20~50°C (-4~122°F) |
| Battery Performance | DC 24V, 3A power adapter |

| | |
|----------------------|--|
| Lamp life | 5 years, more than 30000000 times measurement |
| Display | 7 inch TFT capacity, Touchscreen display |
| Interface | USB, printing port |
| Data Storage | Standard 1000 pcs,sample 20000 pcs |
| Language | Chinese, English, traditional Chinese |
| Standard Accessories | Power Adapter, User Guide,Quality Management Software (download from the official website),USB cable,0% calibration box, measuring aperture. |
| Optional Accessory | Mini printer, Test Fixture, Standard Haze Sheet, Footswitch |
| Size | 290x211x511 mm |
| Weight | About 7.6 kg |



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com