

CONDUCTIVITY METER LTMET12-2



CONDUCTIVITY METER LTMET12-2

LTMET12-2 CONDUCTIVITY METER



SPECIFICATIONS

Model	LTMET12-2
Conductivity	
Range	0.00 μ S/cm to 200 mS/cm
Resolution	1.01 μ S/cm minimum; changed with range
Accuracy	\pm 1.0 % FS
Reference Temperature	25 °C
Standard Recognition	84 μ S/cm, 1413 μ S/cm; 12.88 mS/cm
TDS	
Range	0.00 mg/L ~100 g/L
Resolution	0.01mg/L minimum; changed with range
Accuracy	\pm 1.0% FS
Temperature	
Range	- 5 to 110 °C, 23 to 230 °F
Unit	°C,
Resolution	0.1
Accuracy	\pm 0.2
Measurement	
Reading Mode	AutoRead, Continuous
Reading Prompts	Reading, Stable, Locked
Temp. Compensation	ATC, MTC
Data Management	
Data Storage	50 results each
Inputs	
Temp./EC. Probe	5-pin aviation connector
Display Options	
Backlight	Yes
Auto Shutdown	300, 600, 1200, 1800, 3600sec, off
IP Rating	IP54

General	
Power	AC Adapter,100-240 V AC
Dimensions	242 x 195 x 68 mm
Weight	900 g(1.98 lb)



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com