

# COLORIMETER LTMET13-5



# COLORIMETER LTMET13-5

## LTMET13-5 COLORIMETER



### SPECIFICATIONS

Model	LTMET13-5
Optical Geometry	8°/D
Standards compliant	CIE No.15, GB/T 3978
Sensor	Silicon Photoelectric Diode Array
Measuring Aperture	Φ 8 mm flat, Φ 4 mm sharp
Color Space	CIE LAB, LCh,XYZ, CIE RGB,CIE LUV
Observer	CIE 10° Standard observer
Illuminant	D65,A,C,D50,F2,F6,F7,F8,F10,F11,F12
Displayed Data	Chromaticity Values, Color Difference Values, Pass/Fail Result, Color Offset/Deviation Direction
Measurement Time	1.5 s
Repeatability	$\Delta E^*_{ab}$ 0.03
Inter-instrument agreement	$\Delta E^*_{ab}$ Within 0.4 (average value for measuring BCRA series II 12pcs palettes)
Size	205x67x80 mm
Weight	500 g
Battery Performance	Rechargeable Li-on Battery, 3.7V@3200 m A h
Lamp Life	5 years, more than 1.6 million measurements
Display	TFT Color 2.8inch@ (16:9)
Interface	USB
Data Storage	Standard: 100, Sample: 20000
Operating Environment	0~40 °C (32~104 °F)
Storage Environment	- 20~50 °C (-4~122 °F)
PC Software	CQCS3 software
Standard Accessories	Power adapter, manual, quality management software (official website download), USB cable, wristband
Optional Accessories	Micro Printer, Powder Test Box



**Labtare Analytical Instruments**

Email: [info@labtare.com](mailto:info@labtare.com) | Website: [labtare.com](http://labtare.com)