

COLORIMETER LTMET13-6



COLORIMETER LTMET13-6

LTMET13-6 COLORIMETER



SPECIFICATIONS

Model	LTMET13-6
Optical Geometry	45°/0°
Standards compliant	CIE No.15, GB/T 3979
Sensor	Silicon Photoelectric Diode Array
Measuring Aperture	Φ 20 mm
Color Space	CIE LAB,XYZ, LCh
Observer	CIE 10° Standard observer
Illuminant	D65
Displayed Data	Chromaticity Values, Color Difference Values, Pass/Fail Result, Color Offset/Deviation Direction
Measurement Time	1.5 s
Repeatability	ΔE^*ab Within 0.08 (average value for 30 times)
Inter-instrument agreement	ΔE^*ab Within 0.4 (average value for measuring BCRA series II 12pcs palettes)
Size	205x67x80 mm
Weight	About 400g(including battery)
Battery Performance	Rechargeable Li-on Battery, 3.7 V @ 3200 mAh
Lamp Life	5 years, more than 1.6 million measurements
Display	TFT Color 2.8inch@ (16:9)
Interface	USB
Data Storage	Standard: 100, Sample: 20000
Operating Environment	1~40 °C (32~104 °F)
Storage Environment	- 20~50 °C (-4~122 °F)
PC Software	CQCS3 software
Standard Accessories	Power adapter, manual, quality management software (official website download), USB cable, wristband
Optional Accessories	Micro Printer, Powder Test Box



Labtare Analytical Instruments

Email: info@labtare.com | Website: labtare.com